

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form	: Mixture
Trade name	: BUBBLE GUM #EU55167F
UFI	: QMTQ-SCXV-700T-VH8A
Product code	: EU55167F
Type of product	: Perfumes, fragrances
Product group	: Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Industrial/Professional use spec	: Industrial For professional use only
Use of the substance/mixture	: Perfumes, fragrances
Function or use category	: Odour agents

1.3. Details of the supplier of the safety data sheet

FRENCH COLOR & FRAGRANCE INTERNATIONAL GmbH
Mittlerer Weg 35
DE 79424 Auggen
Germany
T 49-7631-931-8900
SDS@frenchcolor.com, www.frenchcolor.com

1.4. Emergency telephone number

Emergency number	: 1-800-255-3924; +01-813-248-0585; China:+400-120-0751; Mexico:+01-800-099-0731; Brazil: +0-800-591-6042; India: +000-800-100-4086
------------------	--

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Serious eye damage/eye irritation, Category 2	H319
Skin sensitisation, Category 1	H317
Hazardous to the aquatic environment – Chronic Hazard, Category 3	H412

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



GHS07

Signal word (CLP)

: Warning

Contains

: Orange oil ; Methyl salicylate; Eugenol; Cinnamic alcohol; Aldehyde C-16; Linalool; Cinnamic aldehyde

Hazard statements (CLP)

: H317 - May cause an allergic skin reaction.
H319 - Causes serious eye irritation.
H412 - Harmful to aquatic life with long lasting effects.

BUBBLE GUM #EU55167F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Precautionary statements (CLP) : P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 - Wash hands, forearms and face thoroughly after handling.
P272 - Contaminated work clothing should not be allowed out of the workplace.
P273 - Avoid release to the environment.
P280 - Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P302+P352 - IF ON SKIN: Wash with plenty of water.

2.3. Other hazards

Contains no PBT and/or vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

Component	
Substance(s) not included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605	Methyl salicylate (119-36-8)

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
isopentyl acetate substance with national workplace exposure limit(s) (AT, BE, BG, CY, DE, DK, EE, ES, FI, FR, GI, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, NO, CH, TR); substance with a Community workplace exposure limit	CAS-No.: 123-92-2 EC-No.: 204-662-3 EC Index-No.: 607-130-00-2 REACH-no: 01-2119548408-32	2.3 – 4.64	Flam. Liq. 3, H226
Ethyl vanillin	CAS-No.: 121-32-4 EC-No.: 204-464-7 REACH-no: 01-211958961-24	1.71 – 3.545478288	Eye Irrit. 2, H319
Orange oil	CAS-No.: 8008-57-9 EC-No.: 232-433-8 REACH-no: 01-2119493353-35	1.6 – 3.25	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Skin Sens. 1, H317 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 2, H411
Methyl salicylate	CAS-No.: 119-36-8 EC-No.: 204-317-7 EC Index-No.: 607-749-00-8	1.1 – 2.14	Acute Tox. 4 (Oral), H302 Eye Dam. 1, H318 Skin Sens. 1B, H317 Repr. 2, H361d Aquatic Chronic 3, H412
Eugenol	CAS-No.: 97-53-0 EC-No.: 202-589-1 REACH-no: 01-2119971802-33	0.7 – 1.32	Acute Tox. 4 (Oral), H302 Eye Irrit. 2, H319 Skin Sens. 1B, H317

BUBBLE GUM #EU55167F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Menthol Crystals	CAS-No.: 1490-04-6 EC-No.: 216-074-4	0.6 – 1.24	Skin Irrit. 2, H315 Eye Irrit. 2, H319
Cinnamic alcohol	CAS-No.: 104-54-1 EC-No.: 203-212-3 REACH-no: 01-2119934496-29	0.3 – 0.6	Acute Tox. 4 (Oral), H302 Skin Sens. 1B, H317
Aldehyde C-16	CAS-No.: 77-83-8 EC-No.: 201-061-8 REACH-no: 01-2119967770-28	0.3 – 0.6	Skin Sens. 1B, H317 Aquatic Chronic 2, H411
Benzyl acetate substance with national workplace exposure limit(s) (BE, DK, ES, IE, LT, LV, PT, RO)	CAS-No.: 140-11-4 EC-No.: 205-399-7 REACH-no: 01-2119638272-42	0.3 – 0.57	Aquatic Chronic 3, H412
Linalool	CAS-No.: 78-70-6 EC-No.: 201-134-4 EC Index-No.: 603-235-00-2 REACH-no: 01-2119474016-42	0.3 – 0.55	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1B, H317
Cinnamic aldehyde	CAS-No.: 104-55-2 EC-No.: 203-213-9 EC Index-No.: 606-155-00-6 REACH-no: 01-2119935242-45	0.2 – 0.33	Acute Tox. 4 (Dermal), H312 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1A, H317 Aquatic Chronic 3, H412
Isoamyl alcohol substance with national workplace exposure limit(s) (AT, BE, BG, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IT, LT, LU, LV, NL, PL, PT, RO, SE, SI, SK, NO, CH, TR)	CAS-No.: 123-51-3 EC-No.: 204-633-5	0.1 – 0.1	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335
citral substance with national workplace exposure limit(s) (BE, ES, IE, PL, PT)	CAS-No.: 5392-40-5 EC-No.: 226-394-6 EC Index-No.: 605-019-00-3 REACH-no: 01-2119462829-23	0 – 0.09	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317
Benzaldehyde substance with national workplace exposure limit(s) (BG, FI, HU, LT, LV, PL)	CAS-No.: 100-52-7 EC-No.: 202-860-4 EC Index-No.: 605-012-00-5 REACH-no: 01-2119455540-44	0 – 0.03	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Repr. 2, H361 STOT SE 3, H335
Alcohol C-8 substance with national workplace exposure limit(s) (BG, DE, LT, LV, RO, SI, CH)	CAS-No.: 111-87-5 EC-No.: 203-917-6	0 – 0.02	Eye Irrit. 2, H319 Aquatic Chronic 3, H412
Diphenyl oxide substance with national workplace exposure limit(s) (AT, BE, BG, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GI, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, NO, CH, TR); substance with a Community workplace exposure limit	CAS-No.: 101-84-8 EC-No.: 202-981-2 REACH-no: 01-2119472545-33	0 – 0.02	Eye Irrit. 2, H319 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Alcohol C-10 substance with national workplace exposure limit(s) (BG, DE, LT, LV, RO, CH)	CAS-No.: 112-30-1 EC-No.: 203-956-9	0 – 0.01	Aquatic Chronic 3, H412

BUBBLE GUM #EU55167F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Dipropylene glycol monomethyl ether substance with national workplace exposure limit(s) (AT, BE, BG, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GI, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, NO, CH, TR); substance with a Community workplace exposure limit	CAS-No.: 34590-94-8 EC-No.: 252-104-2	0 – 0.0002032	Not classified
Toluene substance with national workplace exposure limit(s) (AT, BE, BG, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GI, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, NO, CH, TR); substance with a Community workplace exposure limit	CAS-No.: 108-88-3 EC-No.: 203-625-9 EC Index-No.: 601-021-00-3	≤ 0.0000024	Not classified

Specific concentration limits:		
Name	Product identifier	Specific concentration limits (%)
Cinnamic aldehyde	CAS-No.: 104-55-2 EC-No.: 203-213-9 EC Index-No.: 606-155-00-6 REACH-no: 01-2119935242-45	(0.001 < C < 0.01) EUH208 (0.01 ≤ C < 0.1) Skin Sens. 1; H317 (0.1 ≤ C < 100) Skin Sens. 1A; H317

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Allow affected person to breathe fresh air. Allow the victim to rest.
First-aid measures after skin contact	: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. If skin irritation or rash occurs: Get medical advice/attention. Specific treatment (see Get medical advice/attention. on this label). If skin irritation occurs: Get medical advice/attention. Wash with plenty of water/.... Get medical advice/attention. Wash contaminated clothing before reuse.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Causes serious eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media	: Do not use a heavy water stream.

BUBBLE GUM #EU55167F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

5.2. Special hazards arising from the substance or mixture

No additional information available

5.3. Advice for firefighters

- Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

- Emergency procedures : Evacuate unnecessary personnel.

For emergency responders

- Protective equipment : Equip cleanup crew with proper protection.
- Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

6.4. Reference to other sections

See Section 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. Avoid breathing dust/fume/gas/mist/vapours/spray.
- Hygiene measures : Wash hands thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container closed when not in use.
- Incompatible products : Strong bases. Strong acids.
- Incompatible materials : Sources of ignition. Direct sunlight.
- Storage temperature : 25 °C
- Storage area : Store in a well-ventilated place. Store away from heat.
- Special rules on packaging : Store in a closed container.
- Packaging materials : Do not store in corrodable metal.

Germany

- Storage class (LGK, TRGS 510) : LGK 12 - Non-combustible liquids

BUBBLE GUM #EU55167F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Joint storage table

LGK 1	LGK 2A	LGK 2B	LGK 3	LGK 4.1A
LGK 4.1B	LGK 4.2	LGK 4.3	LGK 5.1A	LGK 5.1B
LGK 5.1C	LGK 5.2	LGK 6.1A	LGK 6.1B	LGK 6.1C
LGK 6.1D	LGK 6.2	LGK 7	LGK 8A	LGK 8B
LGK 10	LGK 11	LGK 12	LGK 13	LGK 10-13

Joint storage not permitted for

: LGK 1, LGK 6.2, LGK 7

Joint storage with restrictions permitted for

: LGK 4.1A, LGK 4.3, LGK 5.1C

Joint storage permitted for

: LGK 2A, LGK 2B, LGK 3, LGK 4.1B, LGK 4.2, LGK 5.1A, LGK 5.1B, LGK 5.2, LGK 6.1A, LGK 6.1B, LGK 6.1C, LGK 6.1D, LGK 8A, LGK 8B, LGK 10, LGK 11, LGK 12, LGK 13, LGK 10-13

Switzerland

Storage class (LK)

: LK 10/12 - Liquids

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

National occupational exposure and biological limit values

isopentyl acetate (123-92-2)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	270 mg/m ³
	50 ppm
IOEL STEL	540 mg/m ³
	100 ppm
Austria - Occupational Exposure Limits	
MAK (OEL TWA)	270 mg/m ³ (Pentyl acetate (all isomers))
	50 ppm (Pentyl acetate (all isomers))
MAK (OEL STEL)	540 mg/m ³ (Pentylacetate)
	100 ppm (Pentylacetate)
Belgium - Occupational Exposure Limits	
OEL TWA	270 mg/m ³
	50 ppm
OEL STEL	540 mg/m ³
	100 ppm
Bulgaria - Occupational Exposure Limits	
OEL TWA	270 mg/m ³
	50 ppm
OEL STEL	540 mg/m ³
	100 ppm
Croatia - Occupational Exposure Limits	
GVI (OEL TWA)	270 mg/m ³

BUBBLE GUM #EU55167F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

isopentyl acetate (123-92-2)	
	50 ppm
KGVI (OEL STEL)	540 mg/m ³
	100 ppm
Cyprus - Occupational Exposure Limits	
OEL TWA	270 mg/m ³
	50 ppm
OEL STEL	540 mg/m ³
	100 ppm
Denmark - Occupational Exposure Limits	
OEL TWA	271 mg/m ³ (Amyl acetate, all isomers)
	50 ppm (Amyl acetate, all isomers)
OEL STEL	540 mg/m ³
	100 ppm
Estonia - Occupational Exposure Limits	
OEL TWA	270 mg/m ³
	50 ppm
OEL STEL	540 mg/m ³
	100 ppm
Finland - Occupational Exposure Limits	
HTP (OEL TWA)	270 mg/m ³ (Pentyl acetate)
	50 ppm (Pentyl acetate)
HTP (OEL STEL)	540 mg/m ³
	100 ppm
France - Occupational Exposure Limits	
VME (OEL TWA)	270 mg/m ³ (restrictive limit)
	50 ppm (restrictive limit)
VLE (OEL C/STEL)	540 mg/m ³ (restrictive limit)
	100 ppm (restrictive limit)
Germany - Occupational Exposure Limits (TRGS 900)	
AGW (OEL TWA)	270 mg/m ³
	50 ppm
Gibraltar - Occupational Exposure Limits	
OEL TWA	270 mg/m ³
	50 ppm
OEL STEL	540 mg/m ³
	100 ppm
Greece - Occupational Exposure Limits	
OEL TWA	530 mg/m ³
	100 ppm

BUBBLE GUM #EU55167F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

isopentyl acetate (123-92-2)	
OEL STEL	800 mg/m ³
	150 ppm
Hungary - Occupational Exposure Limits	
AK (OEL TWA)	270 mg/m ³
CK (OEL STEL)	540 mg/m ³
Ireland - Occupational Exposure Limits	
OEL TWA	260 mg/m ³
	50 ppm
OEL STEL	520 mg/m ³
	100 ppm
Italy - Occupational Exposure Limits	
OEL TWA	270 mg/m ³
	50 ppm
OEL STEL	540 mg/m ³
	100 ppm
Latvia - Occupational Exposure Limits	
OEL TWA	270 mg/m ³
	50 ppm
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA)	270 mg/m ³
	50 ppm
TPRV (OEL STEL)	540 mg/m ³
	100 ppm
Luxembourg - Occupational Exposure Limits	
OEL TWA	270 mg/m ³
	50 ppm
OEL STEL	540 mg/m ³
	100 ppm
Malta - Occupational Exposure Limits	
OEL TWA	270 mg/m ³
	50 ppm
OEL STEL	540 mg/m ³
	100 ppm
Netherlands - Occupational Exposure Limits	
TGG-15min (OEL STEL)	530 mg/m ³
	98.1 ppm
Poland - Occupational Exposure Limits	
NDS (OEL TWA)	250 mg/m ³
NDSCh (OEL STEL)	500 mg/m ³

BUBBLE GUM #EU55167F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

isopentyl acetate (123-92-2)	
Portugal - Occupational Exposure Limits	
OEL TWA	270 mg/m ³ (indicative limit value)
	50 ppm (indicative limit value (Pentyl acetate, all isomers))
OEL STEL	540 mg/m ³ (indicative limit value)
	100 ppm (indicative limit value)
Romania - Occupational Exposure Limits	
OEL TWA	270 mg/m ³
	50 ppm
OEL STEL	540 mg/m ³
	100 ppm
Slovakia - Occupational Exposure Limits	
NPHV (OEL TWA)	270 mg/m ³
	50 ppm
NPHV (OEL C)	540 mg/m ³
Slovenia - Occupational Exposure Limits	
OEL TWA	270 mg/m ³
	50 ppm
OEL STEL	540 mg/m ³
	100 ppm
Spain - Occupational Exposure Limits	
VLA-ED (OEL TWA)	270 mg/m ³ (indicative limit value)
	50 ppm (indicative limit value)
VLA-EC (OEL STEL)	540 mg/m ³
	100 ppm
Sweden - Occupational Exposure Limits	
NGV (OEL TWA)	270 mg/m ³
	50 ppm
KGV (OEL STEL)	540 mg/m ³
	100 ppm
Norway - Occupational Exposure Limits	
Grenseverdi (OEL TWA)	260 mg/m ³
	50 ppm
Korttidsverdi (OEL STEL)	325 mg/m ³ (value calculated)
	75 ppm (value calculated)
Switzerland - Occupational Exposure Limits	
MAK (OEL TWA)	260 mg/m ³ (Pentyl acetate all isomers)
	50 ppm (Pentyl acetate all isomers)
KZGW (OEL STEL)	260 mg/m ³ (Pentyl acetate all isomers)
	50 ppm (Pentyl acetate all isomers)

BUBBLE GUM #EU55167F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

isopentyl acetate (123-92-2)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH® TLV® TWA	50 ppm (Pentyl acetate, all isomers)
ACGIH® TLV® STEL	100 ppm (Pentyl acetate, all isomers)
Benzyl acetate (140-11-4)	
Belgium - Occupational Exposure Limits	
OEL TWA	62 mg/m ³
	10 ppm
Denmark - Occupational Exposure Limits	
OEL TWA	61 mg/m ³
	10 ppm
OEL STEL	122 mg/m ³
	20 ppm
Ireland - Occupational Exposure Limits	
OEL TWA	10 ppm
OEL STEL	30 ppm (calculated)
Latvia - Occupational Exposure Limits	
OEL TWA	5 mg/m ³
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA)	5 mg/m ³
Portugal - Occupational Exposure Limits	
OEL TWA	10 ppm
OEL chemical category	A4 - Not Classifiable as a Human Carcinogen
Romania - Occupational Exposure Limits	
OEL TWA	50 mg/m ³
	8 ppm
OEL STEL	80 mg/m ³
	13 ppm
Spain - Occupational Exposure Limits	
VLA-ED (OEL TWA)	62 mg/m ³
	10 ppm
USA - ACGIH - Occupational Exposure Limits	
ACGIH® TLV® TWA	10 ppm
ACGIH chemical category	Not Classifiable as a Human Carcinogen
Isoamyl alcohol (123-51-3)	
Austria - Occupational Exposure Limits	
MAK (OEL TWA)	18 mg/m ³
	5 ppm
MAK (OEL STEL)	37 mg/m ³

BUBBLE GUM #EU55167F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Isoamyl alcohol (123-51-3)	
	10 ppm
Belgium - Occupational Exposure Limits	
OEL TWA	18 mg/m ³
	5 ppm
OEL STEL	37 mg/m ³
	10 ppm
Bulgaria - Occupational Exposure Limits	
OEL TWA	18 mg/m ³
	5 ppm
OEL STEL	37 mg/m ³
	10 ppm
Croatia - Occupational Exposure Limits	
GVI (OEL TWA)	18 mg/m ³
	366 mg/m ³ (regulated under 3-Methyl-1-butanol (3-Methyl-1-butanol))
	5 ppm
KGVI (OEL STEL)	100 ppm (regulated under 3-Methyl-1-butanol (3-Methyl-1-butanol))
	37 mg/m ³
	458 mg/m ³ (regulated under 3-Methyl-1-butanol (3-Methyl-1-butanol))
	10 ppm
	125 ppm (regulated under 3-Methyl-1-butanol (3-Methyl-1-butanol))
Cyprus - Occupational Exposure Limits	
OEL TWA	18 mg/m ³
	5 ppm
OEL STEL	37 mg/m ³
	10 ppm
Czech Republic - Occupational Exposure Limits	
PEL (OEL TWA)	18 mg/m ³
Denmark - Occupational Exposure Limits	
OEL TWA	18 mg/m ³ (Pentanol, all isomers)
	5 ppm (Pentanol, all isomers)
OEL STEL	37 mg/m ³
	10 ppm
Estonia - Occupational Exposure Limits	
OEL TWA	18 mg/m ³
	5 ppm
OEL STEL	37 mg/m ³
	10 ppm
Finland - Occupational Exposure Limits	
HTP (OEL TWA)	18 mg/m ³ (Pentanol)
	5 ppm (Pentanol)

BUBBLE GUM #EU55167F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Isoamyl alcohol (123-51-3)	
HTP (OEL STEL)	37 mg/m ³
	10 ppm
France - Occupational Exposure Limits	
VME (OEL TWA)	18 mg/m ³ (restrictive limit)
	5 ppm (restrictive limit)
VLE (OEL C/STEL)	37 mg/m ³ (restrictive limit)
	10 ppm (restrictive limit)
Germany - Occupational Exposure Limits (TRGS 900)	
AGW (OEL TWA)	73 mg/m ³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
	20 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
Greece - Occupational Exposure Limits	
OEL TWA	18 mg/m ³
	5 ppm
OEL STEL	37 mg/m ³
	10 ppm
Hungary - Occupational Exposure Limits	
AK (OEL TWA)	18 mg/m ³
CK (OEL STEL)	37 mg/m ³
Ireland - Occupational Exposure Limits	
OEL TWA	18 mg/m ³
	5 ppm
OEL STEL	10 mg/m ³
	37 ppm
Italy - Occupational Exposure Limits	
OEL TWA	18 mg/m ³
	5 ppm
OEL STEL	37 mg/m ³
	10 ppm
Latvia - Occupational Exposure Limits	
OEL TWA	18 mg/m ³
	5 ppm
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA)	18 mg/m ³
	5 ppm
TPRV (OEL STEL)	37 mg/m ³
	10 ppm
Luxembourg - Occupational Exposure Limits	
OEL TWA	18 mg/m ³

BUBBLE GUM #EU55167F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Isoamyl alcohol (123-51-3)	
	5 ppm
OEL STEL	37 mg/m ³
	10 ppm
Netherlands - Occupational Exposure Limits	
TGG-8u (OEL TWA)	18 mg/m ³
	5 ppm
TGG-15min (OEL STEL)	37 mg/m ³
	10 ppm
Poland - Occupational Exposure Limits	
NDS (OEL TWA)	18 mg/m ³
NDSch (OEL STEL)	37 mg/m ³
Portugal - Occupational Exposure Limits	
OEL TWA	18 mg/m ³ (indicative limit value)
	5 ppm (indicative limit value)
OEL STEL	37 mg/m ³ (indicative limit value)
	10 ppm (indicative limit value)
Romania - Occupational Exposure Limits	
OEL TWA	18 mg/m ³
	5 ppm
OEL STEL	37 mg/m ³
	10 ppm
Slovakia - Occupational Exposure Limits	
NPHV (OEL TWA)	18 mg/m ³
	5 ppm
NPHV (OEL C)	37 mg/m ³
Slovenia - Occupational Exposure Limits	
OEL TWA	18 mg/m ³
	5 ppm
OEL STEL	37 mg/m ³
	10 ppm
Spain - Occupational Exposure Limits	
VLA-ED (OEL TWA)	18 mg/m ³
	5 ppm
VLA-EC (OEL STEL)	37 mg/m ³
	10 ppm
Sweden - Occupational Exposure Limits	
NGV (OEL TWA)	18 mg/m ³
	5 ppm
KGV (OEL STEL)	37 mg/m ³

BUBBLE GUM #EU55167F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Isoamyl alcohol (123-51-3)	
	10 ppm
OEL chemical category	Skin notation
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA)	366 mg/m ³
	100 ppm
WEL STEL (OEL STEL)	458 mg/m ³
	125 ppm
Norway - Occupational Exposure Limits	
Grenseverdi (OEL TWA)	18 mg/m ³
	5 ppm
Korttidsverdi (OEL STEL)	37 mg/m ³ (value from the regulation)
	10 ppm (value from the regulation)
OEL chemical category	Skin notation
Switzerland - Occupational Exposure Limits	
MAK (OEL TWA)	75 mg/m ³ (Pentanol all isomers except 3-Methyl-1-butanol)
	20 ppm (Pentanol all isomers except 3-Methyl-1-butanol)
KZGW (OEL STEL)	150 mg/m ³ (Pentanol (mixture of isomers) except 3-Methyl-1-butanol)
	40 ppm (Pentanol (mixture of isomers) except 3-Methyl-1-butanol)
USA - ACGIH - Occupational Exposure Limits	
ACGIH® TLV® TWA	100 ppm
ACGIH® TLV® STEL	125 ppm
citral (5392-40-5)	
Belgium - Occupational Exposure Limits	
OEL TWA	32 mg/m ³ (vapor and aerosol)
	5 ppm (vapor and aerosol)
OEL chemical category	Skin
Ireland - Occupational Exposure Limits	
OEL TWA	5 ppm
OEL STEL	15 ppm (calculated)
Poland - Occupational Exposure Limits	
NDS (OEL TWA)	27 mg/m ³
NDSch (OEL STEL)	54 mg/m ³
Portugal - Occupational Exposure Limits	
OEL TWA	5 ppm (inhalable fraction; vapor)
OEL chemical category	Sensitizer dermal, A4 - Not Classifiable as a Human Carcinogen, skin - potential for cutaneous exposure
Spain - Occupational Exposure Limits	
VLA-ED (OEL TWA)	5 ppm (inhalable fraction and vapor)
OEL chemical category	Sensitizer, skin - potential for cutaneous absorption

BUBBLE GUM #EU55167F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

citral (5392-40-5)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH® TLV® TWA	5 ppm (inhalable fraction and vapor)
ACGIH chemical category	Not Classifiable as a Human Carcinogen, Skin - potential significant contribution to overall exposure by the cutaneous route, dermal sensitizer
Dipropylene glycol monomethyl ether (34590-94-8)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	308 mg/m ³
	50 ppm
Remark	Possibility of significant uptake through the skin
Austria - Occupational Exposure Limits	
MAK (OEL TWA)	307 mg/m ³ (mixed isomers)
	50 ppm (mixed isomers)
MAK (OEL STEL)	614 mg/m ³ (isomers mixtures)
	100 ppm (isomers mixtures)
OEL chemical category	Skin notation
Belgium - Occupational Exposure Limits	
OEL TWA	308 mg/m ³
	50 ppm
OEL chemical category	Skin, Skin notation
Bulgaria - Occupational Exposure Limits	
OEL TWA	308 mg/m ³
	50 ppm
Croatia - Occupational Exposure Limits	
GVI (OEL TWA)	308 mg/m ³
	50 ppm
OEL chemical category	Skin notation
Cyprus - Occupational Exposure Limits	
OEL TWA	308 mg/m ³
	50 ppm
OEL chemical category	Skin-potential for cutaneous absorption
Czech Republic - Occupational Exposure Limits	
PEL (OEL TWA)	270 mg/m ³
OEL chemical category	Potential for cutaneous absorption
Denmark - Occupational Exposure Limits	
OEL TWA	309 mg/m ³
	50 ppm
OEL STEL	618 mg/m ³
	100 ppm
OEL chemical category	Potential for cutaneous absorption

BUBBLE GUM #EU55167F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Dipropylene glycol monomethyl ether (34590-94-8)	
Estonia - Occupational Exposure Limits	
OEL TWA	308 mg/m ³
	50 ppm
OEL chemical category	Skin notation
Finland - Occupational Exposure Limits	
HTP (OEL TWA)	310 mg/m ³
	50 ppm
OEL chemical category	Potential for cutaneous absorption
France - Occupational Exposure Limits	
VME (OEL TWA)	308 mg/m ³ (restrictive limit)
	50 ppm (restrictive limit)
OEL chemical category	Risk of cutaneous absorption
Germany - Occupational Exposure Limits (TRGS 900)	
AGW (OEL TWA)	310 mg/m ³ (isomer mixture)
	50 ppm (isomer mixture)
Gibraltar - Occupational Exposure Limits	
OEL TWA	308 mg/m ³
	50 ppm
OEL chemical category	Skin notation
Greece - Occupational Exposure Limits	
OEL TWA	600 mg/m ³
	100 ppm
OEL STEL	900 mg/m ³
	150 ppm
OEL chemical category	skin - potential for cutaneous absorption
Hungary - Occupational Exposure Limits	
AK (OEL TWA)	308 mg/m ³
Ireland - Occupational Exposure Limits	
OEL TWA	308 mg/m ³ ((2-Methoxymethylethoxy)propanol)
	50 ppm ((2-Methoxymethylethoxy)propanol)
OEL STEL	924 mg/m ³ (calculated (2-(2-Methoxypropoxy)-1-propanol)
	150 ppm (calculated (2-(2-Methoxypropoxy)-1-propanol)
OEL chemical category	Potential for cutaneous absorption
Italy - Occupational Exposure Limits	
OEL TWA	308 mg/m ³
	50 ppm
OEL chemical category	skin - potential for cutaneous absorption
Latvia - Occupational Exposure Limits	
OEL TWA	308 mg/m ³

BUBBLE GUM #EU55167F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Dipropylene glycol monomethyl ether (34590-94-8)	
	50 ppm
OEL chemical category	skin - potential for cutaneous exposure
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA)	300 mg/m ³ (2-(2-Methoxypropoxy)-propanol)
	50 ppm (2-(2-Methoxypropoxy)-propanol)
TPRV (OEL STEL)	450 mg/m ³ (2-(2-Methoxypropoxy)-propanol)
	75 ppm (2-(2-Methoxypropoxy)-propanol)
OEL chemical category	Skin notation
Luxembourg - Occupational Exposure Limits	
OEL TWA	308 mg/m ³
	50 ppm
OEL chemical category	Possibility of significant uptake through the skin
Malta - Occupational Exposure Limits	
OEL TWA	308 mg/m ³
	50 ppm
OEL chemical category	Possibility of significant uptake through the skin
Netherlands - Occupational Exposure Limits	
TGG-8u (OEL TWA)	300 mg/m ³
	48.7 ppm
Poland - Occupational Exposure Limits	
NDS (OEL TWA)	240 mg/m ³ (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol and 2-(2-Methoxy-1-methylethoxy)propan-1-ol)
NDSCh (OEL STEL)	480 mg/m ³ (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 2-(2-Methoxy-1-methylethoxy)propan-1-ol)
Portugal - Occupational Exposure Limits	
OEL TWA	308 mg/m ³ (indicative limit value)
	50 ppm (indicative limit value)
OEL STEL	150 ppm
OEL chemical category	skin - potential for cutaneous exposure indicative limit value
Romania - Occupational Exposure Limits	
OEL TWA	308 mg/m ³
	50 ppm
OEL chemical category	Skin notation
Slovakia - Occupational Exposure Limits	
NPHV (OEL TWA)	308 mg/m ³
	50 ppm
OEL chemical category	Potential for cutaneous absorption
Slovenia - Occupational Exposure Limits	
OEL TWA	308 mg/m ³
	50 ppm

BUBBLE GUM #EU55167F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Dipropylene glycol monomethyl ether (34590-94-8)	
OEL STEL	308 mg/m ³
	50 ppm
OEL chemical category	Potential for cutaneous absorption
Spain - Occupational Exposure Limits	
VLA-ED (OEL TWA)	308 mg/m ³ (indicative limit value)
	50 ppm (indicative limit value)
OEL chemical category	skin - potential for cutaneous absorption
Sweden - Occupational Exposure Limits	
NGV (OEL TWA)	300 mg/m ³
	50 ppm
KGV (OEL STEL)	450 mg/m ³
	75 ppm
OEL chemical category	Skin notation
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA)	308 mg/m ³
	50 ppm
WEL STEL (OEL STEL)	924 mg/m ³ (calculated)
	150 ppm (calculated)
OEL chemical category	Potential for cutaneous absorption
Norway - Occupational Exposure Limits	
Grenseverdi (OEL TWA)	300 mg/m ³
	50 ppm
Korttidsverdi (OEL STEL)	375 mg/m ³ (value calculated)
	75 ppm (value calculated)
OEL chemical category	Skin notation
Switzerland - Occupational Exposure Limits	
MAK (OEL TWA)	300 mg/m ³ (aerosol, vapour)
	50 ppm (aerosol, vapour)
KZGW (OEL STEL)	300 mg/m ³ (aerosol, vapour)
	50 ppm (aerosol, vapour)
USA - ACGIH - Occupational Exposure Limits	
ACGIH® TLV® TWA	50 ppm (Dipropylene glycol methyl ether)
Toluene (108-88-3)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	192 mg/m ³
	50 ppm
IOEL STEL	384 mg/m ³
	100 ppm
Remark	Possibility of significant uptake through the skin

BUBBLE GUM #EU55167F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Toluene (108-88-3)	
Austria - Occupational Exposure Limits	
MAK (OEL TWA)	190 mg/m ³
	50 ppm
MAK (OEL STEL)	380 mg/m ³
	100 ppm
OEL chemical category	Skin notation
Belgium - Occupational Exposure Limits	
OEL TWA	77 mg/m ³
	20 ppm
OEL STEL	384 mg/m ³
	100 ppm
OEL chemical category	Skin, Skin notation
Bulgaria - Occupational Exposure Limits	
OEL TWA	192 mg/m ³
	50 ppm
OEL STEL	384 mg/m ³
	100 ppm
Bulgaria - Biological limit values	
BLV	1.6 mmol/mmol Creatinine Parameter: Hippuric acid - Medium: urine - Sampling time: at the end of exposure or end of work shift
Croatia - Occupational Exposure Limits	
GVI (OEL TWA)	192 mg/m ³
	50 ppm
KGVI (OEL STEL)	384 mg/m ³
	100 ppm
OEL chemical category	Skin notation
Croatia - Biological limit values	
BLV	1 mg/l Parameter: Toluene - Medium: blood - Sampling time: at the end of the work shift 20 ppm Parameter: Toluene - Medium: final exhaled air - Sampling time: during exposure 2.5 g/g creatinine Parameter: Hippuric acid - Medium: urine - Sampling time: at the end of the work shift (calculated on the average Creatinine value of 1.2 g/L urine) 1 mg/g creatinine Parameter: o-Cresol - Medium: urine - Sampling time: at the end of the work shift (calculated on the average Creatinine value of 1.2 g/L urine)
Cyprus - Occupational Exposure Limits	
OEL TWA	192 mg/m ³
	50 ppm
OEL STEL	384 mg/m ³
	100 ppm
OEL chemical category	Skin-potential for cutaneous absorption
Czech Republic - Occupational Exposure Limits	
PEL (OEL TWA)	200 mg/m ³

BUBBLE GUM #EU55167F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Toluene (108-88-3)	
OEL chemical category	Potential for cutaneous absorption
Czech Republic - Biological limit values	
BLV	1.6 µmol/mmol Creatinine Parameter: o-Cresol - Medium: urine - Sampling time: end of shift (after hydrolysis) 1000 µmol/mmol Creatinine Parameter: Hippuric acid - Medium: urine - Sampling time: end of shift (exposure testing using the o-Cresol parameter to precisely measure Toluene exposure is needed if the value of Hippuric acid is between 1600 and 2500 mg/g of Creatinine, no additional testing is needed if the Hippuric acid value is >2500 mg/g of Creatinine as work exposure to Toluene will have highly exceeded the PEL value.) 1.5 mg/g creatinine Parameter: o-Cresol - Medium: urine - Sampling time: end of shift (after hydrolysis) 1600 mg/g creatinine Parameter: Hippuric acid - Medium: urine - Sampling time: end of shift (exposure testing using the o-Cresol parameter to precisely measure Toluene exposure is needed if the value of Hippuric acid is between 1600 and 2500 mg/g of Creatinine, no additional testing is needed if the Hippuric acid value is >2500 mg/g of Creatinine as work exposure to Toluene will have highly exceeded the PEL value.)
Denmark - Occupational Exposure Limits	
OEL TWA	94 mg/m ³
	25 ppm
OEL STEL	384 mg/m ³
	100 ppm
OEL chemical category	Potential for cutaneous absorption
Estonia - Occupational Exposure Limits	
OEL TWA	192 mg/m ³
	50 ppm
OEL STEL	384 mg/m ³
	100 ppm
OEL chemical category	Skin notation
Finland - Occupational Exposure Limits	
HTP (OEL TWA)	81 mg/m ³
	25 ppm
HTP (OEL STEL)	380 mg/m ³
	100 ppm
OEL chemical category	Potential for cutaneous absorption
Finland - Biological limit values	
BLV	500 nmol/L Parameter: Toluene - Medium: blood - Sampling time: in the morning after a working day
France - Occupational Exposure Limits	
VME (OEL TWA)	76.8 mg/m ³ (restrictive limit)
	20 ppm (restrictive limit)
VLE (OEL C/STEL)	384 mg/m ³ (restrictive limit)
	100 ppm (restrictive limit)
OEL chemical category	Reproductive Toxin category 2, Risk of cutaneous absorption

BUBBLE GUM #EU55167F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Toluene (108-88-3)	
France - Biological limit values	
BLV	20 µg/l Parameter: Toluene - Medium: blood - Sampling time: end of workweek (Semi-quantitative (ambiguous interpretation)) Parameter: Hippuric acid - Medium: urine - Sampling time: end of shift (per the Authority, the values for this substance must be decided and/or determined on a case by case basis. Guidance for the calculation of and interpretation of values is provided in the source)
Germany - Occupational Exposure Limits (TRGS 900)	
AGW (OEL TWA)	190 mg/m ³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed) 50 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
Chemical category	Skin notation
Germany - Biological limit values (TRGS 903)	
Biological limit value	600 µg/l Parameter: Toluene - Medium: whole blood - Sampling time: immediately after exposure 75 µg/l Parameter: Toluene - Medium: urine - Sampling time: end of exposure or shift 1.5 mg/l Parameter: o-Cresol (after hydrolysis) - Medium: urine - Sampling time: at the end of the shift, in case of long-term exposure after several previous shifts
Gibraltar - Occupational Exposure Limits	
OEL TWA	192 mg/m ³ 50 ppm
OEL STEL	384 mg/m ³ 100 ppm
OEL chemical category	Skin notation
Greece - Occupational Exposure Limits	
OEL TWA	192 mg/m ³ 50 ppm
OEL STEL	384 mg/m ³ 100 ppm
OEL chemical category	skin - potential for cutaneous absorption
Hungary - Occupational Exposure Limits	
AK (OEL TWA)	190 mg/m ³
CK (OEL STEL)	384 mg/m ³
OEL chemical category	Potential for cutaneous absorption
Ireland - Occupational Exposure Limits	
OEL TWA	192 mg/m ³ 50 ppm
OEL STEL	384 mg/m ³ 100 ppm
OEL chemical category	Potential for cutaneous absorption
Italy - Occupational Exposure Limits	
OEL TWA	192 mg/m ³

BUBBLE GUM #EU55167F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Toluene (108-88-3)	
	50 ppm
OEL chemical category	skin - potential for cutaneous absorption
Latvia - Occupational Exposure Limits	
OEL TWA	50 mg/m ³
	14 ppm
OEL chemical category	skin - potential for cutaneous exposure
Latvia - Biological Exposure Indices	
BEI	600 µg/l Parameter: Toluene - Medium: blood - Sampling time: at the end of exposure (for assessment of long-term exposure, samples are taken at the end of a shift after several previous shifts) 75 µg/l Parameter: Toluene - Medium: urine - Sampling time: end of shift (for assessment of long-term exposure, samples are taken at the end of a shift after several previous shifts) 1.5 mg/l Parameter: o-Cresol - Medium: urine - Sampling time: at the end of exposure or shift (after hydrolysis)
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA)	192 mg/m ³
	50 ppm
TPRV (OEL STEL)	384 mg/m ³
	100 ppm
OEL chemical category	Reproductive toxin, Skin notation
Luxembourg - Occupational Exposure Limits	
OEL TWA	192 mg/m ³
	50 ppm
OEL STEL	384 mg/m ³
	100 ppm
OEL chemical category	Possibility of significant uptake through the skin
Malta - Occupational Exposure Limits	
OEL TWA	192 mg/m ³
	50 ppm
OEL STEL	384 mg/m ³
	100 ppm
OEL chemical category	Possibility of significant uptake through the skin
Netherlands - Occupational Exposure Limits	
TGG-8u (OEL TWA)	150 mg/m ³
	39 ppm
TGG-15min (OEL STEL)	384 mg/m ³
	100 ppm
Poland - Occupational Exposure Limits	
NDS (OEL TWA)	100 mg/m ³
NDSch (OEL STEL)	200 mg/m ³

BUBBLE GUM #EU55167F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Toluene (108-88-3)	
Portugal - Occupational Exposure Limits	
OEL TWA	192 mg/m ³ (indicative limit value)
	50 ppm (indicative limit value)
OEL STEL	384 mg/m ³ (indicative limit value)
	100 ppm (indicative limit value)
OEL chemical category	A4 - Not Classifiable as a Human Carcinogen, skin - potential for cutaneous exposure indicative limit value
Romania - Occupational Exposure Limits	
OEL TWA	192 mg/m ³
	50 ppm
OEL STEL	384 mg/m ³
	100 ppm
OEL chemical category	Skin notation
Romania - Biological limit values	
BLV	2 g/l Parameter: Hippuric acid - Medium: urine - Sampling time: end of shift 3 mg/l Parameter: o-Cresol - Medium: urine - Sampling time: end of shift
Slovakia - Occupational Exposure Limits	
NPHV (OEL TWA)	192 mg/m ³
	50 ppm
NPHV (OEL C)	384 mg/m ³ (also biological monitoring considered)
OEL chemical category	Potential for cutaneous absorption
Slovakia - Biological limit values	
BLV	600 µg/l Parameter: Toluene - Medium: blood - Sampling time: end of exposure or work shift 1.5 mg/l Parameter: o-Cresol - Medium: urine - Sampling time: after all work shifts (for long-term exposure) 1.5 mg/l Parameter: o-Cresol - Medium: urine - Sampling time: end of exposure or work shift 2401 mg/g creatinine Parameter: Hippuric acid - Sampling time: end of exposure or work shift
Slovenia - Occupational Exposure Limits	
OEL TWA	192 mg/m ³
	50 ppm
OEL STEL	384 mg/m ³
	100 ppm
OEL chemical category	Category 2, Potential for cutaneous absorption
Spain - Occupational Exposure Limits	
VLA-ED (OEL TWA)	192 mg/m ³ (indicative limit value)
	50 ppm (indicative limit value)
VLA-EC (OEL STEL)	384 mg/m ³
	100 ppm
OEL chemical category	skin - potential for cutaneous absorption

BUBBLE GUM #EU55167F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Toluene (108-88-3)	
Spain - Biological limit values	
BLV	0.6 mg/l Parameter: o-Cresol - Medium: urine - Sampling time: end of shift 0.05 mg/l Parameter: Toluene - Medium: blood - Sampling time: start of last shift of workweek 0.08 mg/l Parameter: Toluene - Medium: urine - Sampling time: end of shift
Sweden - Occupational Exposure Limits	
NGV (OEL TWA)	192 mg/m ³
	50 ppm
KGV (OEL STEL)	384 mg/m ³
	100 ppm
OEL chemical category	Skin notation
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA)	191 mg/m ³
	50 ppm
WEL STEL (OEL STEL)	384 mg/m ³
	100 ppm
WEL chemical category	Potential for cutaneous absorption
Norway - Occupational Exposure Limits	
Grenseverdi (OEL TWA)	94 mg/m ³
	25 ppm
Korttidsverdi (OEL STEL)	141 mg/m ³ (value calculated)
	37.5 ppm (value calculated)
OEL chemical category	Skin notation
Switzerland - Occupational Exposure Limits	
MAK (OEL TWA)	190 mg/m ³
	50 ppm
KZGW (OEL STEL)	760 mg/m ³
	200 ppm
OEL chemical category	Skin notation, Category 2 reproductive toxin
Switzerland - BAT	
BAT	600 µg/l Parameter: Toluene - Medium: whole blood - Sampling time: end of shift 6.48 µmol/l Parameter: Toluene - Medium: whole blood - Sampling time: end of shift 2 g/g creatinine Parameter: Hippuric acid - Medium: urine - Sampling time: end of shift, and after several shifts (for long-term exposures) Parameter: Hippuric acid - Medium: urine - Sampling time: end of shift, and after several shifts (for long-term exposures) 0.5 mg/l Parameter: o-Cresol - Medium: urine - Sampling time: end of shift, and after several shifts (for long-term exposures) 4.62 µmol/l Parameter: o-Cresol - Medium: urine - Sampling time: end of shift, and after several shifts (for long-term exposures) 75 µg/l Parameter: Toluol - Medium: urine - Sampling time: end of shift
USA - ACGIH - Occupational Exposure Limits	
ACGIH® TLV® TWA	20 ppm

BUBBLE GUM #EU55167F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Toluene (108-88-3)	
ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA - ACGIH - Biological Exposure Indices	
BEI	0.02 mg/l Parameter: Toluene - Medium: blood - Sampling time: prior to last shift of workweek 0.03 mg/l Parameter: Toluene - Medium: urine - Sampling time: end of shift 0.3 mg/g creatinine Parameter: o-Cresol with hydrolysis - Medium: urine - Sampling time: end of shift (background)
Benzaldehyde (100-52-7)	
Bulgaria - Occupational Exposure Limits	
OEL TWA	5 mg/m ³
Finland - Occupational Exposure Limits	
HTP (OEL TWA)	4.4 mg/m ³
	1 ppm
HTP (OEL C)	17.4 mg/m ³
	4 ppm
Hungary - Occupational Exposure Limits	
AK (OEL TWA)	5 mg/m ³
CK (OEL STEL)	10 mg/m ³
Latvia - Occupational Exposure Limits	
OEL TWA	5 mg/m ³
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA)	5 mg/m ³
Poland - Occupational Exposure Limits	
NDS (OEL TWA)	10 mg/m ³
NDSch (OEL STEL)	40 mg/m ³
Alcohol C-8 (111-87-5)	
Bulgaria - Occupational Exposure Limits	
OEL TWA	10 mg/m ³
Germany - Occupational Exposure Limits (TRGS 900)	
AGW (OEL TWA)	54 mg/m ³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed (long-chain Alcohols))
	10 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed (long-chain Alcohols))
Latvia - Occupational Exposure Limits	
OEL TWA	10 mg/m ³ (Octanol)
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA)	10 mg/m ³
Romania - Occupational Exposure Limits	
OEL TWA	150 mg/m ³
	28 ppm
OEL STEL	250 mg/m ³

BUBBLE GUM #EU55167F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Alcohol C-8 (111-87-5)	
	47 ppm
OEL chemical category	Skin notation
Slovenia - Occupational Exposure Limits	
OEL TWA	106 mg/m ³
	20 ppm
OEL STEL	106 mg/m ³
	20 ppm
Switzerland - Occupational Exposure Limits	
MAK (OEL TWA)	106 mg/m ³
	20 ppm
KZGW (OEL STEL)	106 mg/m ³
	20 ppm
Diphenyl oxide (101-84-8)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	7 mg/m ³
	1 ppm
IOEL STEL	14 mg/m ³
	2 ppm
Austria - Occupational Exposure Limits	
MAK (OEL TWA)	7 mg/m ³
	1 ppm
MAK (OEL STEL)	14 mg/m ³
	2 ppm
Belgium - Occupational Exposure Limits	
OEL TWA	7 mg/m ³ (vapor)
	1 ppm (vapor)
OEL STEL	14 mg/m ³ (vapor)
	2 ppm (vapor)
Bulgaria - Occupational Exposure Limits	
OEL TWA	7 mg/m ³
	1 ppm
OEL STEL	14 mg/m ³
	2 ppm
Croatia - Occupational Exposure Limits	
GVI (OEL TWA)	7 mg/m ³
	1 ppm
KGVI (OEL STEL)	14 mg/m ³
	2 ppm

BUBBLE GUM #EU55167F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Diphenyl oxide (101-84-8)	
Cyprus - Occupational Exposure Limits	
OEL TWA	7 mg/m ³
	1 ppm
OEL STEL	14 mg/m ³
	2 ppm
Czech Republic - Occupational Exposure Limits	
PEL (OEL TWA)	5 mg/m ³
Denmark - Occupational Exposure Limits	
OEL TWA	7 mg/m ³
	1 ppm
OEL STEL	14 mg/m ³
	2 ppm
Estonia - Occupational Exposure Limits	
OEL TWA	7 mg/m ³
	1 ppm
OEL STEL	14 mg/m ³
	2 ppm
Finland - Occupational Exposure Limits	
HTP (OEL TWA)	7 mg/m ³
	1 ppm
HTP (OEL STEL)	14 mg/m ³
	2 ppm
France - Occupational Exposure Limits	
VME (OEL TWA)	7 mg/m ³ (indicative limit)
	1 ppm (indicative limit)
VLE (OEL C/STEL)	14 mg/m ³ (indicative limit)
	2 ppm (indicative limit)
Germany - Occupational Exposure Limits (TRGS 900)	
AGW (OEL TWA)	7.1 mg/m ³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed-vapor)
	1 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed-vapor)
Gibraltar - Occupational Exposure Limits	
OEL TWA	7 mg/m ³
	1 ppm
OEL STEL	14 mg/m ³
	200 ppm
Greece - Occupational Exposure Limits	
OEL TWA	7 mg/m ³
	1 ppm

BUBBLE GUM #EU55167F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Diphenyl oxide (101-84-8)	
OEL STEL	14 mg/m ³
	2 ppm
Hungary - Occupational Exposure Limits	
AK (OEL TWA)	7 mg/m ³
CK (OEL STEL)	14 mg/m ³
Ireland - Occupational Exposure Limits	
OEL TWA	7 mg/m ³ (vapour)
	1 ppm (vapour)
OEL STEL	14 mg/m ³ (vapor)
	2 ppm (vapor)
Italy - Occupational Exposure Limits	
OEL TWA	7 mg/m ³
	1 ppm
Latvia - Occupational Exposure Limits	
OEL TWA	7 mg/m ³
	1 ppm
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA)	7 mg/m ³
	1 ppm
TPRV (OEL STEL)	14 mg/m ³
	2 ppm
Luxembourg - Occupational Exposure Limits	
OEL TWA	7 mg/m ³
	1 ppm
OEL STEL	14 mg/m ³
	2 ppm
Malta - Occupational Exposure Limits	
OEL TWA	7 mg/m ³
	1 ppm
OEL STEL	14 mg/m ³
	2 ppm
Netherlands - Occupational Exposure Limits	
TGG-8u (OEL TWA)	7 mg/m ³
	1 ppm
TGG-15min (OEL STEL)	14 mg/m ³
	2 ppm
Poland - Occupational Exposure Limits	
NDS (OEL TWA)	7 mg/m ³
NDSCh (OEL STEL)	14 mg/m ³

BUBBLE GUM #EU55167F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Diphenyl oxide (101-84-8)	
Portugal - Occupational Exposure Limits	
OEL TWA	7 mg/m ³ (indicative limit value)
	1 ppm (indicative limit value-vapor)
OEL STEL	14 mg/m ³ (indicative limit value)
	2 ppm (indicative limit value-vapor)
Romania - Occupational Exposure Limits	
OEL TWA	7 mg/m ³
	1 ppm
OEL STEL	14 mg/m ³
	2 ppm
Slovakia - Occupational Exposure Limits	
NPHV (OEL TWA)	7 mg/m ³
	1 ppm
NPHV (OEL C)	14 mg/m ³
Slovenia - Occupational Exposure Limits	
OEL TWA	7 mg/m ³
	1 ppm
OEL STEL	14 mg/m ³
	2 ppm
Spain - Occupational Exposure Limits	
VLA-ED (OEL TWA)	7.1 mg/m ³ (vapor)
	1 ppm (vapor)
VLA-EC (OEL STEL)	14.2 mg/m ³ (vapor)
	2 ppm (vapor)
Sweden - Occupational Exposure Limits	
NGV (OEL TWA)	7 mg/m ³
	1 ppm
KGV (OEL STEL)	14 mg/m ³
	2 ppm
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA)	7 mg/m ³
	1 ppm
WEL STEL (OEL STEL)	14 mg/m ³
	2 ppm
Norway - Occupational Exposure Limits	
Grenseverdi (OEL TWA)	7 mg/m ³
	1 ppm
Korttidsverdi (OEL STEL)	14 mg/m ³ (value from the regulation)
	2 ppm (value from the regulation)

BUBBLE GUM #EU55167F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Diphenyl oxide (101-84-8)	
Switzerland - Occupational Exposure Limits	
MAK (OEL TWA)	7 mg/m ³ (aerosol, vapour)
	1 ppm (aerosol, vapour)
KZGW (OEL STEL)	14 mg/m ³ (aerosol, vapour)
	2 ppm (aerosol, vapour)
OEL chemical category	Category 2 reproductive toxin
USA - ACGIH - Occupational Exposure Limits	
ACGIH® TLV® TWA	1 ppm (vapor)
ACGIH® TLV® STEL	2 ppm (vapor fraction)
Alcohol C-10 (112-30-1)	
Bulgaria - Occupational Exposure Limits	
OEL TWA	10 mg/m ³
Germany - Occupational Exposure Limits (TRGS 900)	
AGW (OEL TWA)	66 mg/m ³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
	10 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
Latvia - Occupational Exposure Limits	
OEL TWA	10 mg/m ³
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA)	10 mg/m ³
Romania - Occupational Exposure Limits	
OEL TWA	100 mg/m ³
	15 ppm
OEL STEL	200 mg/m ³
	30 ppm
Switzerland - Occupational Exposure Limits	
MAK (OEL TWA)	66 mg/m ³ (aerosol, vapour)
	10 ppm (aerosol, vapour)
KZGW (OEL STEL)	66 mg/m ³ (aerosol, vapour)
	10 ppm (aerosol, vapour)

8.2. Exposure controls

Personal protection equipment

Personal protective equipment:

Avoid all unnecessary exposure.

Personal protective equipment symbol(s):



BUBBLE GUM #EU55167F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Eye and face protection

Eye protection:

Chemical goggles or safety glasses

Skin protection

Hand protection:

Wear protective gloves.

Respiratory protection

Respiratory protection:

Wear appropriate mask

Environmental exposure controls

Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Conforms to standard.
Odour	: characteristic.
Odour threshold	: Not available
Melting point	: Not available
Freezing point	: Not available
Boiling point	: Not available
Flammability	: Not applicable, Non flammable.
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: 68 °C
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: Not available
Solubility	: Not available
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: 0.031575181 mm Hg (calculated value)
Vapour pressure at 50°C	: Not available
Density	: Not available
Relative density	: Not available
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

9.2. Other information

Other safety characteristics

VOC content : 89.2706296 % (calculated value)(CARB VOC) (%w/w)

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Not established.

10.3. Possibility of hazardous reactions

Not established.

BUBBLE GUM #EU55167F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Ethyl vanillin (121-32-4)

LD50 oral rat	1590 mg/kg (Source: NLM_CIP)
LD50 oral	3000 mg/kg bodyweight
LD50 dermal rat	> 2000 mg/kg (Source: ECHA_API)

Orange oil (8008-57-9)

LD50 oral rat	4400 mg/kg (Source: NZ_CCID)
LD50 dermal rabbit	> 5000 mg/kg (Source: CHEMVIEW)

Methyl salicylate (119-36-8)

LD50 oral rat	887 mg/kg (Source: NLM_CIP)
LD50 oral	890 mg/kg bodyweight
LD50 dermal rabbit	> 5000 mg/kg (Source: NLM_CIP)

Eugenol (97-53-0)

LD50 oral rat	1930 mg/kg (Source: NZ_CCID)
LD50 oral	2500 mg/kg bodyweight
LC50 Inhalation - Rat	> 2.58 mg/l/4h

Menthol Crystals (1490-04-6)

LD50 oral	2500 mg/kg bodyweight
LD50 dermal rabbit	> 5000 mg/kg (Source: NLM_HSDB)
LC50 Inhalation - Rat	5289 mg/m ³ (Exposure time: 4 h Source: ECHA_API)
LC50 Inhalation - Rat (Dust/Mist)	5.3 mg/l/4h

Cinnamic alcohol (104-54-1)

LD50 oral	2000 mg/kg bodyweight
LD50 dermal rabbit	> 5000 mg/kg (Source: ECHA_API)

Aldehyde C-16 (77-83-8)

LD50 oral rat	5470 mg/kg (Source: NLM_CIP)
LD50 dermal rat	> 2000 mg/kg (Source: ECHA_API)

BUBBLE GUM #EU55167F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Benzyl acetate (140-11-4)	
LD50 oral rat	2490 mg/kg (Source: JAPAN_GHS)
LD50 oral	2490 mg/kg bodyweight
LD50 dermal rabbit	> 5000 mg/kg (Source: JAPAN_GHS)
Linalool (78-70-6)	
LD50 oral rat	2790 mg/kg (Source: NLM_CIP)
LD50 oral	2790 mg/kg
LD50 dermal rabbit	5610 mg/kg (Source: ECHA_API)
Cinnamic aldehyde (104-55-2)	
LD50 oral rat	2220 mg/kg (Source: NLM_CIP)
LD50 oral	2220 mg/kg
LD50 dermal rabbit	1260 mg/kg (Source: EPA_HPVS)
LD50 dermal	1260 mg/kg
Isoamyl alcohol (123-51-3)	
LD50 oral rat	5770 mg/kg (Source: AU_WES)
LD50 oral	4000 mg/kg bodyweight
LD50 dermal rabbit	3250 mg/kg (Source: JAPAN_GHS)
LD50 dermal	3216 mg/kg bodyweight
LC50 Inhalation - Rat [ppm]	> 2000 ppm (Exposure time: 8 h Source: AU_WES)
citral (5392-40-5)	
LD50 oral rat	4960 mg/kg (Source: NLM_CIP)
LD50 dermal rabbit	2250 mg/kg (Source: NLM_CIP)
Dipropylene glycol monomethyl ether (34590-94-8)	
LD50 oral rat	5.35 g/kg (Source: NLM_HSDB)
LD50 dermal rabbit	9500 mg/kg (Source: NLM_CIP)
Toluene (108-88-3)	
LD50 oral rat	2600 mg/kg (Source: JAPAN_GHS)
LD50 dermal rabbit	12000 mg/kg (Source: JAPAN_GHS)
LC50 Inhalation - Rat	12.5 mg/l/4h
Benzaldehyde (100-52-7)	
LD50 oral rat	1292 mg/kg (Source: JAPAN_GHS)
LD50 dermal rabbit	> 1250 mg/kg (Source: JAPAN_GHS)
LC50 Inhalation - Rat	< 5 mg/l/4h
Alcohol C-8 (111-87-5)	
LD50 oral rat	> 5000 mg/kg (Source: ECHA)
LD50 dermal rabbit	> 5 g/kg (Source: NLM_HSDB)
Diphenyl oxide (101-84-8)	
LD50 oral rat	2450 mg/kg (Source: NLM_CIP)

BUBBLE GUM #EU55167F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Diphenyl oxide (101-84-8)	
LD50 oral	2830 mg/kg bodyweight
LD50 dermal rabbit	> 7940 mg/kg (Source: NLM_CIP)
LC50 Inhalation - Rat (Dust/Mist)	1.5 mg/l/4h

Alcohol C-10 (112-30-1)	
LD50 oral rat	4720 mg/kg (Source: NZ_CCID)
LD50 dermal rat	> 5000 mg/kg (Source: ECHA_API)
LC50 Inhalation - Rat	> 71 mg/l (Exposure time: 1 h Source: ECHA_API)

Skin corrosion/irritation	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Carcinogenicity	: Not classified
Additional information	: Based on available data, the classification criteria are not met

Eugenol (97-53-0)	
IARC group	3 - Not classifiable

Benzyl acetate (140-11-4)	
IARC group	3 - Not classifiable

Toluene (108-88-3)	
IARC group	3 - Not classifiable

Reproductive toxicity	: Not classified
Additional information	: Based on available data, the classification criteria are not met
STOT-single exposure	: Not classified
Additional information	: Based on available data, the classification criteria are not met

Isoamyl alcohol (123-51-3)	
STOT-single exposure	May cause respiratory irritation.

Benzaldehyde (100-52-7)	
STOT-single exposure	May cause respiratory irritation.

STOT-repeated exposure	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Aspiration hazard	: Not classified
Additional information	: Based on available data, the classification criteria are not met

Toluene (108-88-3)	
Hydrocarbon	Yes

11.2. Information on other hazards

Other information

Potential adverse human health effects and symptoms	: Based on available data, the classification criteria are not met
---	--

SECTION 12: Ecological information

12.1. Toxicity

Ecology - water	: Harmful to aquatic life with long lasting effects.
-----------------	--

BUBBLE GUM #EU55167F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Harmful to aquatic life with long lasting effects.

Ethyl vanillin (121-32-4)	
LC50 - Fish [1]	81.4 – 94.3 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)
Eugenol (97-53-0)	
LC50 - Fish [1]	13 mg/l (Exposure time: 96 h - Species: Danio rerio [semi-static] Source: ECHA)
Menthol Crystals (1490-04-6)	
LC50 - Fish [1]	22.3 mg/l (Exposure time: 96 h - Species: Brachydanio rerio [static] Source: IUCLID)
Aldehyde C-16 (77-83-8)	
LC50 - Fish [1]	4.2 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [semi-static] Source: ECHA)
Linalool (78-70-6)	
LC50 - Fish [1]	27.8 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static] Source: ECHA)
EC50 - Crustacea [1]	20 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 96h - Algae [1]	88.3 mg/l (Species: Desmodesmus subspicatus)
Isoamyl alcohol (123-51-3)	
LC50 - Fish [1]	700 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static] Source: ECHA)
EC50 - Crustacea [1]	260 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 72h - Algae [1]	493 mg/l (Species: Desmodesmus subspicatus)
EC50 96h - Algae [1]	181 mg/l (Species: Desmodesmus subspicatus)
citral (5392-40-5)	
EC50 - Crustacea [1]	7 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 72h - Algae [1]	16 mg/l (Species: Desmodesmus subspicatus)
EC50 96h - Algae [1]	19 mg/l (Species: Desmodesmus subspicatus)
Dipropylene glycol monomethyl ether (34590-94-8)	
LC50 - Fish [1]	> 10000 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 - Crustacea [1]	1919 mg/l (Exposure time: 48 h - Species: Daphnia magna)
Toluene (108-88-3)	
LC50 - Fish [1]	15.22 – 19.05 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)
LC50 - Fish [2]	12.6 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static] Source: EPA)
EC50 - Crustacea [1]	5.46 – 9.83 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
EC50 - Crustacea [2]	11.5 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 72h - Algae [1]	12.5 mg/l (Species: Pseudokirchneriella subcapitata [static])
EC50 96h - Algae [1]	> 433 mg/l (Species: Pseudokirchneriella subcapitata)
Benzaldehyde (100-52-7)	
LC50 - Fish [1]	10.6 – 11.8 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through] Source: EPA)

BUBBLE GUM #EU55167F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Benzaldehyde (100-52-7)	
LC50 - Fish [2]	12.69 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static] Source: IUCLID)
Alcohol C-8 (111-87-5)	
LC50 - Fish [1]	11.4 – 12.9 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)
LC50 - Fish [2]	17.68 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static] Source: EPA)
Alcohol C-10 (112-30-1)	
LC50 - Fish [1]	2.2 – 2.5 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)
LC50 - Fish [2]	4.12 – 6.2 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static] Source: EPA)
EC50 - Crustacea [1]	3 mg/l (Exposure time: 48 h - Species: Daphnia magna)
12.2. Persistence and degradability	
BUBBLE GUM #EU55167F	
Persistence and degradability	May cause long-term adverse effects in the environment.
isopentyl acetate (123-92-2)	
Persistence and degradability	Rapidly degradable
Ethyl vanillin (121-32-4)	
Persistence and degradability	Not established.
Orange oil (8008-57-9)	
Persistence and degradability	Rapidly degradable
Methyl salicylate (119-36-8)	
Persistence and degradability	Rapidly degradable
Eugenol (97-53-0)	
Persistence and degradability	Rapidly degradable
Menthol Crystals (1490-04-6)	
Persistence and degradability	Rapidly degradable
Cinnamic alcohol (104-54-1)	
Persistence and degradability	Rapidly degradable
Aldehyde C-16 (77-83-8)	
Persistence and degradability	Rapidly degradable
Benzyl acetate (140-11-4)	
Persistence and degradability	Rapidly degradable
Linalool (78-70-6)	
Persistence and degradability	Rapidly degradable
Cinnamic aldehyde (104-55-2)	
Persistence and degradability	Rapidly degradable

BUBBLE GUM #EU55167F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Isoamyl alcohol (123-51-3)	
Persistence and degradability	Rapidly degradable
citral (5392-40-5)	
Persistence and degradability	Rapidly degradable
Dipropylene glycol monomethyl ether (34590-94-8)	
Persistence and degradability	Rapidly degradable
Toluene (108-88-3)	
Persistence and degradability	Rapidly degradable
Benzaldehyde (100-52-7)	
Persistence and degradability	Rapidly degradable
Alcohol C-8 (111-87-5)	
Persistence and degradability	Rapidly degradable
Diphenyl oxide (101-84-8)	
Persistence and degradability	Rapidly degradable
Alcohol C-10 (112-30-1)	
Persistence and degradability	Rapidly degradable
12.3. Bioaccumulative potential	
BUBBLE GUM #EU55167F	
Bioaccumulative potential	Not established.
isopentyl acetate (123-92-2)	
Partition coefficient n-octanol/water (Log Pow)	2.7 (at 35 °C)
Ethyl vanillin (121-32-4)	
Partition coefficient n-octanol/water (Log Pow)	1.61 (at 25 °C)
Bioaccumulative potential	Not established.
Orange oil (8008-57-9)	
Partition coefficient n-octanol/water (Log Pow)	$\geq 2.78 - \leq 4.88$
Methyl salicylate (119-36-8)	
Partition coefficient n-octanol/water (Log Pow)	2.55
Eugenol (97-53-0)	
Partition coefficient n-octanol/water (Log Pow)	1.83 (at 30 °C (at pH 5.5))
Menthol Crystals (1490-04-6)	
BCF - Fish [1]	0.5 – 15
Partition coefficient n-octanol/water (Log Pow)	3.79 (at 25 °C)
Cinnamic alcohol (104-54-1)	
Partition coefficient n-octanol/water (Log Pow)	1.636 (at 27 °C (at pH 3.52))

BUBBLE GUM #EU55167F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Aldehyde C-16 (77-83-8)	
Partition coefficient n-octanol/water (Log Pow)	2.4 (at 25 °C (cis isomer))
Benzyl acetate (140-11-4)	
Partition coefficient n-octanol/water (Log Pow)	1.96 (at 25 °C (at pH 7))
Linalool (78-70-6)	
Partition coefficient n-octanol/water (Log Pow)	2.9 (at 20 °C (at pH 7))
Cinnamic aldehyde (104-55-2)	
Partition coefficient n-octanol/water (Log Pow)	2.1065 (at 25 °C)
Isoamyl alcohol (123-51-3)	
Partition coefficient n-octanol/water (Log Pow)	1.35 (at pH 6.5)
citral (5392-40-5)	
Partition coefficient n-octanol/water (Log Pow)	2.76 (at 25 °C)
Dipropylene glycol monomethyl ether (34590-94-8)	
Partition coefficient n-octanol/water (Log Pow)	0.35 (at 25 °C (at pH 7))
Toluene (108-88-3)	
Partition coefficient n-octanol/water (Log Pow)	2.73 (at 20 °C (at pH 7))
Benzaldehyde (100-52-7)	
BCF - Fish [1]	(no significant bioaccumulation)
Partition coefficient n-octanol/water (Log Pow)	1.4 (at 25 °C)
Alcohol C-8 (111-87-5)	
Partition coefficient n-octanol/water (Log Pow)	3.5 (at 23 °C (at pH 5.7))
Diphenyl oxide (101-84-8)	
BCF - Fish [1]	(470 dimensionless)
Partition coefficient n-octanol/water (Log Pow)	4.21 (at 25 °C)
Alcohol C-10 (112-30-1)	
Partition coefficient n-octanol/water (Log Pow)	4.5 (at 25 °C (at pH 6))
12.4. Mobility in soil	
No additional information available	
12.5. Results of PBT and vPvB assessment	
No additional information available	
12.6. Endocrine disrupting properties	
No additional information available	
12.7. Other adverse effects	
BUBBLE GUM #EU55167F	
Other information	Avoid release to the environment.

BUBBLE GUM #EU55167F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Ethyl vanillin (121-32-4)

Other information

Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container in accordance with local/national laws and regulations.

Ecological waste information : Avoid release to the environment.

HP Code : HP14 - "Ecotoxic:" waste which presents or may present immediate or delayed risks for one or more sectors of the environment

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.2. UN proper shipping name				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.3. Transport hazard class(es)				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
No supplementary information available				

14.6. Special precautions for user

Overland transport

Not applicable

Transport by sea

Not applicable

Air transport

Not applicable

Inland waterway transport

Not applicable

Rail transport

Not applicable

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

BUBBLE GUM #EU55167F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (2024/590)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 2024/590 on substances that deplete the ozone layer)

Council Regulation (EC) for the control of dual-use items

Contains no substance subject to the COUNCIL REGULATION (EC) for the control of dual-use items

VOC Directive (2004/42)

VOC content : 89.2706296 % (calculated value)(CARB VOC) (%w/w)

Explosives Precursors Regulation (EU 2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (EC 273/2004)

Contains substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

Name	CN designation	CAS-No.	CN code	Category, Subcategory	Threshold	Annex
Toluene		108-88-3	2902 30 00	Category 3		Annex I

National regulations

Austria

Toxic Substances Ordinance 2000 : Is not subject to the Toxic Substances Ordinance 2000.

France

Occupational diseases	
Code	Description
RG 4 BIS	Gastrointestinal disorders caused by benzene, toluene, xylenes and all products containing them
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide

Germany

VOC ordinance (ChemVOCFarbV) : VOC content : 89.2706296 % (calculated value)(CARB VOC) (%w/w)

Water hazard class (WGK) : WGK 2, Significantly hazardous to water (Classification according to AwSV, Annex 1).

List of sensitizing substances (TRGS 907) : Contains sensitizing substances according TRGS 907.

BUBBLE GUM #EU55167F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Major Accidents Ordinance (12. BImSchV) : Is not subject to the Major Accidents Ordinance (12. BImSchV)

Netherlands

ABM category : A(2) - toxic for aquatic organisms, may have longterm hazardous effects in aquatic environment
SZW-lijst van kankerverwekkende stoffen : Orange oil is listed
SZW-lijst van mutagene stoffen : Orange oil is listed
SZW-lijst van reprotoxische stoffen – Borstvoeding : None of the components are listed
SZW-lijst van reprotoxische stoffen – Vruchtbaarheid : None of the components are listed
SZW-lijst van reprotoxische stoffen – Ontwikkeling : Methyl salicylate, Toluene are listed

Denmark

Class for fire hazard : Class III-1
Store unit : 50 liter
Classification remarks : Flammable according to the Danish Ministry of Justice; Emergency management guidelines for the storage of flammable liquids must be followed
Danish National Regulations : Young people below the age of 18 years are not allowed to use the product
Pregnant/breastfeeding women working with the product must not be in direct contact with the product

Poland

Polish National Regulations : Act of 25 February 2011 on chemical substances and their mixtures (J. o L. No. 63, item 322 as amended; consolidated text J. o L. 2019, item 1225).
Act of 14 December 2012 on waste (J. o L. 2013, item 322 as amended; consolidated text J. o L. 2020, item 797).
The announcement of Marshal of the Sejm of the Republic of Poland dated 19 October 2016 concerning the consolidated text announcement of the decree on the management of packaging and packaging waste (J. o L. 2016, item 1863 as amended).
Decree of the Minister of Environment of 14 December 2014 on the catalogue of waste (J. o L. 2014, item 1923).
Act of 19 August 2011 on the Carriage of Dangerous Goods (J. o L. 2011 No. 227, item 1367 as amended; consolidated text J. o L. 2020, item 154).
Regulation of the Minister of Family, Labour and Social Policy of 12 June 2018 on the highest permissible concentration and intensity of noxious agents for health at work environment (J. o L. item 1286 as amended).
The announcement of Minister of Health dated 9 September 2016 concerning the consolidated text announcement of the decree of the Minister of Health of 30 December 2004 on health and safety at work related to exposure to chemical agents at work (J. o L. of 16 September 2016, item 1488)
Regulation of the Minister of Health of 2 February 2011 on tests and measurements of the noxious agents for health at work environment (J. o L. No. 33, item 166 as amended).
Regulation of the Minister of Environment of 9 December 2003 on particularly hazardous substances to the environment (J. o L. No. 217, item 2141).
ADR Agreement: Government Statement of 13 March 2023 on the entry into force of amendments to Annexes A and B to the Agreement concerning the International Carriage of Dangerous Goods by Road (ADR), signed in Geneva on 30 September 1957 (J. o. L. 2023, item 891)

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.
Other information : None.

BUBBLE GUM #EU55167F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:	
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
EUH208	Contains {0}message≤name of sensitising substance>{fieldvalue=_SENSITIZER_COMPONENTS}. May produce an allergic reaction.
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Repr. 2	Reproductive toxicity, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1A	Skin sensitisation, category 1A
Skin Sens. 1B	Skin sensitisation, category 1B
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H361	Suspected of damaging fertility or the unborn child.
H361d	Suspected of damaging the unborn child.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

The classification complies with : ATP 12

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.